

## Technical data sheet

# $\pmb{ev} guard^{\circledR} \ black-opaque \ 9005$ EVA interlayer for laminated safety, security & architectural glass



| Stability*   |                                |       |          |
|--|--------------------------------|-------|----------|
| Ball drop test                                     | DIN 52338                      | 44.2  |          |
|  | DIN EN 356                     | 44.3  | P1A      |
| Pendulum test                                      | DIN EN 12600                   | 44.1  | 1B1      |
| Resistance against heat, humidity and UV radiation | DIN EN ISO 12543-4             | 44.1  | арргочес |
| DiBt – Deutsches Institut für Bautechni            | k AbZ (national technical appr | oval) | approved |
| American National Standard Institute               | ANSI Z97.1 incl. ASTM G 155    | -05a  | арргочес |
|  | ASTM D 100                     |       |          |
|  | ASTM E 313-                    | -10   |          |
|  | ASTM E 308                     |       |          |
| Salt spray test (3,000 hours)                      | ASTM B117 / ISO 9227           | 44.2  | арргочес |
|  | DIN EN ISO 10140-2             | 44.2  | 37 db    |



#### **Processing**

| Minimum temperature | 105 °C (220 F)                           |
|---------------------|--|
| Maximum temperature | 160 °C (320 F)                           |
| Production process  | Vacuum / Nip-roll – Autoclave lamination |

### Dimensions & Packaging

| Thickness | min. 0.2 mm, max. 1.14 mm  |  |
|-----------|----------------------------|--|
| Width     | min. 800 mm, max. 2,400 mm | <ul> <li>Customized dimensions and</li> <li>packaging on individual</li> </ul> |
| Core      | 76 mm cardboard core       | request  |
| Packaging | in cardboard boxes         | -  |

national technical approval (AbZ) by







| Properties          | Test method | non cross-linked     |                        | cross-linked* |  |  |
|---------------------|-------------|----------------------|------------------------|---------------|--|--|
| Density             | ISO 1183    | 0.95-0.97 g/cm³      |                        |               | m³   |  |
| Optical appearance  |             | black-opaque matt    |                        | black-        | black-opaque                                     |  |
| Tensile strength    | ISO 527-3   | MD<br>CD             | > 5 N/mm²<br>> 5 N/mm² | MD<br>CD      | > 20 N/mm <sup>2</sup><br>> 20 N/mm <sup>2</sup> |  |
| Elongation at break | ISO 527-3   | MD<br>CD             | > 700 %<br>> 700 %     | MD<br>CD      | > 400 %<br>> 400 %                               |  |
| Hardness            | DIN 53505   |                      | > 65 S                 | Shore A       |  |  |
| Refractive Index    |             |                      |                        | 1.48          |  |  |
| Optical density     |             | ca. 5 (for 0,380 mm) |                        |               |  |  |
|                     |             |                      |                        |               |  |  |

 $<sup>\</sup>ensuremath{^{*}}$  values depend on appropriate lamination



| Storage recommendation |  |  |
|------------------------|--|--|
| Temperature            | < 30 °C (85 F)   |  |
| Humidity               | < 80 %   |  |
| Shelf life             | use by 12 months after date of production<br>Opened rolls have to be protected against direct sunlight and dust. |  |



**Folienwerk Wolfen GmbH** Guardianstraße 4 06766 Bitterfeld-Wolfen Germany T +49 (0)3494 6979 0 F +49 (0)3494 6979 37 info@folienwerk-wolfen.de www.folienwerk-wolfen.de



www.evguard.de/en

#### Disclaimer

Our information about our products and processes is based on extensive research and our considerable experience in the field of applied engineering. We provide this information, which to the best of our knowledge is correct, orally and in writing. In doing so, we do not assume any liability other than the liability agreed upon in the respective individual contract, and we reserve the right to make technical modifications in the course of our product development. However, this shall not release user from its obligation to verify the suitability of our products and processes for its own use. Purchaser's specifications of intended use shall only be binding, if we, at the time of contract conclusion, have confirmed in writing that the delivered goods are suitable for the use intended by Purchaser. This shall also apply to the protection of third party industrial property rights and to applications and processes.